



FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

Revision date: 24.05.2019

# SAFETY DATA SHEET according to 1907/2006/EC, Article 31

# 1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

#### **Product details**

Trade name: Cabin Dry HS Express Clear Coat

**Article number:** 11805, 11808

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Intended use: Car refinishing Product/Clear coating material, Varnish

Manufacturer/Supplier: Chamäleon GmbH

Rudolf-Diesel-Straße, 8a, 69115 Heidelberg -- Germany

**Further information obtainable from:** Product Safety Department **Information in case of emergency:** + 49 70024112112 (CH)

## 2 – HAZARDS IDENTIFICATION

Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

## Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.





FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE

WEB WWW.CHAMAELEON-PRODUKTION.DE

## Hazard pictograms



GHS02 GHS07 GHS09

**Signal word:** Warning

## Hazard-determining components of labelling:

n-Butyl acetate

2-Methoxy-1-methylethyl acetate

Reaction mass of pentamethyl-piperidyl sebacate Pentaerythritol tetrakis(3-mercaptopropionate)

## **Hazard statements**

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

## **Precautionary statements:**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

## **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

Other hazards

Results of PBT and vPvB assessment

**PBT:**Not applicable. **vPvB:**Not applicable.

# 3- COMPOSITION/INFORMATION ON INGREDIENTS

**Chemical characterization: Mixtures** 

**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 123-86-4	n-Butyl acetate	25-50%
EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	Flam. Liq. 3, H226; STOT SE 3, H336	
CAS: 763-69-9	ethyl 3-ethoxypropionate	2.5-<10%

CHAMÄLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440

FAX 0049 (0) 6221 - 520 449 MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

EINECS: 212-112-9 Reg.nr.: 01-2119463267-34	Flam. Liq. 3, H226	
CAS: 110-12-3 EINECS: 203-737-8	5-methylhexan-2-one	2.5-<10%
Reg.nr.: 01-2119472300-51	Flam. Liq. 3, H226; Acute Tox. 4, H332	
CAS: 108-65-6	2-Methoxy-1-methylethyl acetate	2.5-<10%
EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	Flam. Liq. 3, H226;STOT SE 3, H336	
EC number: 915-687-0	Reaction mass of pentamethyl-piperidyl sebacate	≥0.25-<1%
Reg.nr.: 01-2119491304-40	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	
CAS: 7575-23-7	Pentaerythritol tetrakis(3-mercaptopropionate)	≥0.1-<0.25%
EINECS: 231-472-8 Reg.nr.: 01-2119486981-23	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Sens. 1A, H317	

## **Additional information:**

For the wording of the listed risk phrases refer to section 16.

## <u>4– FIRST - AID MEASURE</u>

## **Description of first aid measures**

**After inhalation:** Supply fresh air; consult doctor in case of complaints.

## After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Generally the product does not irritate the skin.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: If symptoms persist consult doctor.

# Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

**Information for doctor:** 

## 5- FIRE - FIGHTING MEASURE

## **Extinguishing media**

Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture No further relevant information available.

Advice for firefighters

**Protective equipment:** No special measures required.



FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

## 6- ACCIDENTAL RELEASE MEASURE

# Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

# **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

## Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

## Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7- HANDLING AND STORAGE

## Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

# Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

# Conditions for safe storage, including any incompatibilities

#### Storage.

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions: Keep container tightly sealed.

**Storage class: 3** 

**Specific end use(s):** No further relevant information available.

## <u>8 – EXPOSURE CONTROLS / PERSONAL PROTECTION</u>

Additional information about design of technical facilities: No further data; see item 7.

## **Control parameters**

Ingredients with limit values that require monitoring at the workplace:	
123-86-4 n-Butyl acetate	
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm
110-12-3 5-methylhexan-2-one	



FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

WEL	Short-term value: 475 mg/m³, 100 ppm Long-term value: 95 mg/m³, 20 ppm Sk	
108-65-6 2	-Methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk	

**Additional information:** The lists valid during the making were used as basis.

**Exposure controls** 

Personal protective equipment:

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

**Respiratory protection:** 

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

**Protection of hands:** 

Protective gloves (EN 374)

**Material of gloves:** 

Butyl rubber, BR

Recommended thickness of the material: ≥0.7 mm

Breakthrough time of glove material

For the mixture of chemicals the penetration time has to be at least 60 minutes (Permeation according to EN 374 Part 3: Level 3).

**Eye protection:** 

Tightly sealed goggles

## 9 – PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties		
General Information		
Appearance:		
Form:	Fluid	
Colour:	According to product specification	
Odour:	Characteristic	
Odour threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	Undetermined.	
Initial boiling point and boiling range:	124 °C	
Flash point:	27 °C (DIN EN ISO 1523:2002)	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	370 °C (DIN 51794)	

CHAMÄLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

<b>Decomposition temperature:</b>	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<b>Explosion limits:</b>	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
Vapour pressure at 20 °C:	10.7 hPa
Density at 20 °C:	1.005 g/cm³ (DIN EN ISO 2811-1)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	20-23 s (DIN 53211/4)
Solvent content:	
VOC (EC)	41.84 %
Solids content (weight-%):	58.2 %
Other information	No further relevant information available.

## 10-STABILITY AND REACTIVITY

**Reactivity** No further relevant information available.

**Chemical stability** 

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

**Incompatible materials:** No further relevant information available.

Hazardous decomposition products: Carbon monoxide.

# <u>11– TOXILOGICAL INFORMATION</u>

# **Information on toxicological effects**

Acute toxicity Based on available data, the classification criteria are not met.



FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

LD/LC50 values relevant for classification:		
7575-23-7 Pentaerythritol tetrakis(3-mercaptopropionate)		
Oral	LD50	1,000-2,000 mg/kg (rat)

## **Primary irritant effect:**

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

## Respiratory or skin sensitisation

May cause an allergic skin reaction.

# CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

# STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

# 12 – ECOLOGICAL INFORMATION

## **Toxicity**

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

**Bioaccumulative potential** No further relevant information available.

Mobility in soil No further relevant information available.

**Ecotoxical effects:** 

**Remark:** Harmful to fish

Additional ecological information:

#### **General notes:**

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

## Results of PBT and vPvB assessment

**PBT:** Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

## 13- DISPOSAL CONSIDERATION

## Waste treatment methods

#### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.



FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

European waste catalogue

waste paint and varnish containing organic solvents or other hazardous substances

**Uncleaned packaging:** 

**Recommendation:** Disposal must be made according to official regulations.

# <u>14– TRANSPORT INFORMATION</u>

**UN-Number** 

ADR, IMDG, IATA UN1263

UN proper shipping name

**ADR** UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS **IMDG** PAINT (Polythiols, benzotriazole derivative), MARINE

**POLLUTANT** 

**IATA PAINT** 

Transport hazard class(es)

**ADR** 



Class 3 (F1) Flammable liquids. Label

**IMDG** 





Class 3 Flammable liquids. Label

**IATA** 



Class 3 Flammable liquids. Label 3



FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

Packing group

ADR, IMDG, IATA III

**Environmental hazards:** Product contains environmentally hazardous substances:

bis-(1,2,2,6,6-penthamethyl-4-piperidyl)sebacate

**Marine pollutant:** Yes

Symbol (fish and tree)

**Special marking (ADR):** Symbol (fish and tree)

**Special precautions for user** Warning: Flammable liquids.

Danger code (Kemler): 30
EMS Number: F-E,S-E
Stowage Category: A

Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

**Transport/Additional information:** 

**ADR** 

Transport category 3
Tunnel restriction code D/E

**IMDG** 

Limited quantities (LQ) 5L

UN "Model Regulation": UN 1263 PAINT, 3, III, ENVIRONMENTALLY

**HAZARDOUS** 

## <u>15 – REGULATORY INFORMATION</u>

Safety, health and environmental regulations/legislation specific for the substance or mixture: Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

**National regulations:** 

Class	Share in %
NK	25-50

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



CHAMALEON

CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

# <u>16-OTHER INFORMATION</u>

## **Relevant phrases**

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

# Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

## Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European

Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.